

L Teflon heater

EXCELLENT CHEMICAL RESISTANCE TO AGGRESSIVE ACIDS

Compatible with virtually any chemistry. Excellent chemical resistance to aggressive acids! Low profile, bottom design. Inert to most solutions with a corrosion resistant head. Low watt density. Built-in thermal protector and grounded element. Corrosion-resistant head. 500-6000 watts, 120- 480 volts.



FEATURES

Inert to most aqueous acids, alkaline, anodizing, & picking solutions.

Rugged, heavy wall PTFE covered stainless steel element reduces permeation. Guaranteed 100% pinhole free.

Space saving & long service life with low Watt density design of 10 W/in² (1.5 W/cm²).

Vapor-resistant, flame retardant polypropylene terminal enclosure with 3 ft (.9m) flexible PVC liquid tight conduit.

Lower watt densities for highly viscous solutions & technical acids.

Optional patented purge feature promotes longer heater life.



Volts:
120 to 480 Volts



Watts:
500 to 6,000 watts



Certification:
cULus CE (except 600 volts)

HXFL SERIES, LOW PROFILE L-SHAPED FLUOROPOLYMER (PTFE) HEATERS

WATTS	VOLTS	HOT ZONE in/(mm)	STD. VERT. LENGTH in/(mm)	DIA. in/(mm)	MAX. COLD ZONE in/(mm)	MODEL NUMBER	SHIP WGT. lbs/(kg)
500	120	5	12	5	36	HXFL5105-R*..**	6
	240	(127)	(305)	(127)	(914)	HXFL5205-R*..**	(2.7)
1000	120	6	12	6	36	HXFL1106-R*..**	7
	240	(152)	(305)	(152)	(914)	HXFL1206-R*..**	(3.2)
2000	120	8	18	8	35	HXFL2108-R*..**	8
	240	(203)	(457)	(203)	(889)	HXFL2208-R*..**	(3.6)
	480					HXFL2408-R*..**	
3000	240	9	18	9	35	HXFL3209-R*..**	13
	480	(229)	(457)	(229)	(889)	HXFL3409-R*..**	(5.9)
4000	240	11	18	11	35	HXFL4211-R*..**	15
	480	(279)	(457)	(279)	(889)	HXFL4411-R*..**	(6.8)
5000	240	12	18	12	31	HXFL5212-R*..**	18
	480	(305)	(457)	(305)	(787)	HXFL5412-R*..**	(8.2)
6000	240	13	18	13	25	HXFL6213-R*..**	22
	480	(330)	(457)	(330)	(635)	HXFL6413-R*..**	(10)


Single phase only. Guards recommended. This configuration is not recommended for electroless chemistry, phosphoric acid, or applications prone to sludge buildup.

L Teflon heater

SPECIFICATIONS

Wattages	500 Watts to 6,000 Watts
Voltages	120 Volts to 480 Volts
Safety Features	<p>Grounded internal metal element</p> <p>Built-in thermal protector. Replaceable PI protector . Other options available.</p> <p>Non-floating construction</p>

DETAILS



MODEL NUMBER BREAKDOWN

Series	Wattage	Voltage	Diameter (in.)	Vertical Length (in.)	Type of Protector	Wire & Conduit Length
HXFL = PTFE	.5 = 500	1 = 120	05 = .5kW	R12 = .5kW	Replaceable Fuse	36" length standard (no designator)
	1 = 1000	2 = 240	06 = 1kW	R12 = 1kW	P1 (std) = solutions up to 190°F	Specify variations from standard Ex: -X84 = 84"
	2 = 2000	3 = 380	08 = 2kW	R18 = 2kW	Resettable Fuse	
	3 = 3000	4 = 480	09 = 3kW	R18 = 3kW	P2 = solutions up to 190°F	
	4 = 4000	5 = 415	11 = 4kW	R18 = 4kW	P8 = solutions up to 210°F	
	5 = 5000	6 = 600	12 = 5kW	R18 = 5kW	P3 = solutions up to 250°F	
	6 = 6000	7 = 400	13 = 6kW	R18 = 6kW		
		8 = 208		Specify custom lengths		
		9 = 220				
		0 = 200				