



Teflon heater

EXCELLENT CHEMICAL RESISTANCE TO AGGRESSIVE ACIDS

Compatible with virtually any chemistry. Excellent chemical resistance to aggressive acids! Low profile, bottom design. Inert to most solutions with a corrosion resistant head. Low watt density. Built-in thermal protector and grounded element. Corrosion-resistant head. 500-5000 watts, 120- 480 volts.



FEATURES

Inert to most aqueous acids, alkaline, anodizing, & picking solutions.

Rugged, heavy wall PTFE covered stainless steel element reduces permeation. Guaranteed 100% pinhole free.

Space saving & long service life with low Watt density design of 10 W/in² (1.5 W/cm²).

Vapor-resistant, flame retardant polypropylene terminal enclosure with 3 ft (.9m) flexible PVC liquid tight conduit.

Lower watt densities for highly viscous solutions & technical acids.

Optional patented purge feature promotes longer heater life.



Volts:
120 to 480 Volts



Watts:
500 to 5,000 watts



Certification:
cULus CE (except 600 volts)

HXFL SERIES, LOW PROFILE L-SHAPED FLUOROPOLYMER (PTFE) HEATERS

WATTS	VOLTS	HOT ZONE in/(mm)	STD. VERT. LENGTH in/(mm)	DIA. in/(mm)	MAX. COLD ZONE in/(mm)	MODEL NUMBER	SHIP WGT. lbs/(kg)
500	120	5	12	5	36	HXFL5105-R*..**	6
	240	(127)	(305)	(127)	(914)	HXFL5205-R*..**	(2.7)
1000	120	6	12	6	36	HXFL1106-R*..**	7
	240	(152)	(305)	(152)	(914)	HXFL1206-R*..**	(3.2)
2000	120	8	18	8	35	HXFL2108-R*..**	8
	240	(203)	(457)	(203)	(889)	HXFL2208-R*..**	(3.6)
	480					HXFL2408-R*..**	
3000	240	9	18	9	35	HXFL3209-R*..**	13
	480	(229)	(457)	(229)	(889)	HXFL3409-R*..**	(5.9)
4000	240	11	18	11	35	HXFL4211-R*..**	15
	480	(279)	(457)	(279)	(889)	HXFL4411-R*..**	(6.8)
5000	240	12	18	12	31	HXFL5212-R*..**	18
	480	(305)	(457)	(305)	(787)	HXFL5412-R*..**	(8.2)
6000	240	13	18	13	25	HXFL6213-R*..**	22
	480	(330)	(457)	(330)	(635)	HXFL6413-R*..**	(10)

Single phase only. Guards recommended. This configuration is not recommended for electroless chemistry, phosphoric acid, or applications prone to sludge buildup.

Teflon heater

SPECIFICATIONS

Wattages	500 Watts to 5,000 Watts
Voltages	120 Volts to 480 Volts
Safety Features	Grounded internal metal element Built-in thermal protector. Replaceable PI protector . Other options available. Non-floating construction

DETAILS

