



# Teflon heater

## EXCELLENT CHEMICAL RESISTANCE TO AGGRESSIVE ACIDS

Compatible with virtually any chemistry. Excellent chemical resistance to aggressive acids! Low profile, bottom design. Inert to most solutions with a corrosion resistant head. Low watt density. Built-in thermal protector and grounded element. Corrosion-resistant head. 500-5000 watts, 120- 480 volts.



### FEATURES

Inert to most aqueous acids, alkaline, anodizing, & picking solutions.

Rugged, heavy wall PTFE covered stainless steel element reduces permeation. Guaranteed 100% pinhole free.

Space saving & long service life with low Watt density design of 10 W/in<sup>2</sup> (1.5 W/cm<sup>2</sup>).

Vapor-resistant, flame retardant polypropylene terminal enclosure with 3 ft (.9m) flexible PVC liquid tight conduit.

Lower watt densities for highly viscous solutions & technical acids.

Optional patented purge feature promotes longer heater life.



Volts:  
120 to 480 Volts



Watts:  
500 to 5,000 watts



Certification:  
cULus CE (except  
600 volts)

HXFL SERIES, LOW PROFILE L-SHAPED FLUOROPOLYMER (PTFE) HEATERS								
WATTS	VOLTS	HOT ZONE in/(mm)	STD. VERT. LENGTH in/(mm)	DIA. in/(mm)	MAX. COLD ZONE in/(mm)	MODEL NUMBER	SHIP WGT. lbs/(kg)	
500	120	5	12	5	36	HXFL5105-R*..**	6	
	240	(127)	(305)	(127)	(914)	HXFL5205-R*..**	(2.7)	
1000	120	6	12	6	36	HXFL1106-R*..**	7	
	240	(152)	(305)	(152)	(914)	HXFL1206-R*..**	(3.2)	
2000	120	8	18	8	35	HXFL2108-R*..**	8	
	240	(203)	(457)	(203)	(889)	HXFL2208-R*..**	(3.6)	
	480					HXFL2408-R*..**		
3000	240	9	18	9	35	HXFL3209-R*..**	13	
	480	(229)	(457)	(229)	(889)	HXFL3409-R*..**	(5.9)	
4000	240	11	18	11	35	HXFL4211-R*..**	15	
	480	(279)	(457)	(279)	(889)	HXFL4411-R*..**	(6.8)	
5000	240	12	18	12	31	HXFL5212-R*..**	18	
	480	(305)	(457)	(305)	(787)	HXFL5412-R*..**	(8.2)	
6000	240	13	18	13	25	HXFL6213-R*..**	22	
	480	(330)	(457)	(330)	(635)	HXFL6413-R*..**	(10)	

Single phase only. Guards recommended. This configuration is not recommended for electroless chemistry, phosphoric acid, or applications prone to sludge buildup.

# Teflon heater

## SPECIFICATIONS

Wattages	500 Watts to 5,000 Watts
Voltages	120 Volts to 480 Volts
Safety Features	Grounded internal metal element  Built-in thermal protector. Replaceable PI protector . Other options available.  Non-floating construction

## DETAILS

