



Teflon heater

EXCELLENT CHEMICAL RESISTANCE TO AGGRESSIVE ACIDS

Compatible with virtually any chemistry. Excellent chemical resistance to aggressive acids! Low profile, bottom design. Inert to most solutions with a corrosion resistant head. Low watt density. Built-in thermal protector and grounded element. Corrosion-resistant head. 500-5000 watts, 120- 480 volts.



FEATURES

Inert to most aqueous acids, alkaline, anodizing, & picking solutions.

Rugged, heavy wall PTFE covered stainless steel element reduces permeation. Guaranteed 100% pinhole free.

Space saving & long service life with low Watt density design of 10 W/in² (1.5 W/cm²).

Vapor-resistant, flame retardant polypropylene terminal enclosure with 3 ft (.9m) flexible PVC liquid tight conduit.

Lower watt densities for highly viscous solutions & technical acids.

Optional patented purge feature promotes longer heater life.



Volts:
120 to 480 Volts



Watts:
500 to 5,000 watts



Certification:
cULus CE (except
600 volts)

HXFL SERIES, LOW PROFILE L-SHAPED FLUOROPOLYMER (PTFE) HEATERS

WATTS	VOLTS	HOT ZONE in/(mm)	STD. VERT. LENGTH in/(mm)	DIA. in/(mm)	MAX. COLD ZONE in/(mm)	MODEL NUMBER	SHIP WGT. lbs/(kg)
500	120	5	12	5	36	HXFL5105-R*..**	6
	240	(127)	(305)	(127)	(914)	HXFL5205-R*..**	(2.7)
1000	120	6	12	6	36	HXFL1106-R*..**	7
	240	(152)	(305)	(152)	(914)	HXFL1206-R*..**	(3.2)
2000	120	8	18	8	35	HXFL2108-R*..**	8
	240	(203)	(457)	(203)	(889)	HXFL2208-R*..**	(3.6)
	480					HXFL2408-R*..**	
3000	240	9	18	9	35	HXFL3209-R*..**	13
	480	(229)	(457)	(229)	(889)	HXFL3409-R*..**	(5.9)
4000	240	11	18	11	35	HXFL4211-R*..**	15
	480	(279)	(457)	(279)	(889)	HXFL4411-R*..**	(6.8)
5000	240	12	18	12	31	HXFL5212-R*..**	18
	480	(305)	(457)	(305)	(787)	HXFL5412-R*..**	(8.2)
6000	240	13	18	13	25	HXFL6213-R*..**	22
	480	(330)	(457)	(330)	(635)	HXFL6413-R*..**	(10)

Single phase only. Guards recommended. This configuration is not recommended for electroless chemistry, phosphoric acid, or applications prone to sludge buildup.

